

5.12 kWh

Solar System Optimization

10Year Warranty Exterior Rated & Stackable

W FEATURES

- 10 year warranty
- Ultra safe LFP material
- Short circuit protection
- Built for saftey
- Wide range inverter compatibility
- Parallel up to 16 modules
- Load shifting
- Multi protection to avoid over discharge
- Smart BMS management for longer lifespan
- Active balancing charging, low self consumption







| Model | VB 5100 |
|------------------------------|---|
| Cell Type | LFP |
| Rated Power | 5.12kWh |
| Rated Capacity | 100Ah |
| Rated Voltage | 51.2V |
| Charge Voltage | 56.5V |
| Max Charge/Discharge Current | 100A |
| Discharge Peak Current | 105A / 15s, 120A / |
| Parallel | Up to 16 units parallelable |
| Protection Rating | IP65 |
| Dimension | 27 1/4"W * 15 5/8"H * 6 3/4"D 2" H Base |
| Weight | 112 lbs |
| Communication | CAN/RS485 |
| Compatible Inverter | Victron, Luxpower, Deye, Voltronic, SMA, Goodwe, Growatt, Sofar, Solark, Victron, Solis, Megarevo, Growatt |
| Humidity | 5%~85% RH |
| Work Temperature | -4°F ~ 131°F |
| Storage Temperature | 14°F ~ 95°F |
| Built-in BMS | Battery voltage, current, temperature, and State of Charge (SOC) |
| Certification | 10 year, 6000 cycles UL- UL1973 and UN38.3 |
| | UL 9540 UL 9540A 0.5C, 80%DOD |
| Protection | Over charge/discharge/current/voltage/temperature protection Short circuit protection, Reverse connection protection Charge balance, Low SOC protection |
| Solar Energy Distributors | |